



Dell PowerEdge T310

The Dell™ PowerEdge™ T310 server delivers enterprise-level performance, redundancy, and comprehensive right-sized manageability options in a 1-socket tower that is simple to own, deploy, and manage.

Dell's robust and reliable 1-socket tower server, the PowerEdge T310, offers the performance of DDR3 memory, advanced systems management options, and the availability of up to four hard drives (3.5" or 2.5") in a compact tower chassis.

Right-Sized, Flexible Technology and Business Value

The Dell PowerEdge T310 was designed to meet the needs of your growing small business or remote office by offering more features and performance than a basic, entry-level server. Customizable with optional advanced systems management capabilities including remote management, a short 20.5 inch chassis, redundancy features, and cost-effective RAID options, the T310 is the ideal robust and reliable 1-socket tower server.

Dell aims to add value to your business by providing the features you need. Our goal is to deliver value through tailored solutions based on industry standards, as well as purposeful, innovative design.

Purposeful Design

The PowerEdge T310, part of the 11th Generation PowerEdge server portfolio, is built with system design commonality and reliability. All 11th Generation servers are built with user ease in mind. All external ports, power supplies, LEDs, and LCD screens are kept in the same location for familiar user experience and easy installation and deployment.

Robust, metal hard drive carriers and organized cabling are designed to improve component access and airflow across the server. The PowerEdge T310's purposeful design provides quiet acoustics and an optional interactive LCD screen positioned on the front by the bezel for ease of monitoring. With a chassis depth of 20.5", the PowerEdge T310's chassis is ideal for use in a back office, retail, or small office setting where space and acoustics matter.

Energy-Optimized Technology

Energy Smart technologies are at the core system level on the PowerEdge T310. These energy-optimized technologies are designed to increase energy efficiency within the server while continuing to deliver the performance your business requires. Built with lower wattage power supplies than its predecessor, the PowerEdge T310 offers highly efficient cabled or redundant power supply options. Also included in the T310 are highly efficient fans, designed to spin faster in accordance with server workload demands and help reduce unnecessary noise when possible. In addition, the logical component layout aids with airflow direction, helping to keep the server cool.

Simplified Systems Management

The Lifecycle Controller is the engine for advanced embedded management and is delivered as part of the optional iDRAC Express or iDRAC Enterprise in the PowerEdge T310. The Lifecycle Controller helps to deliver faster server deployment and update capabilities from a bare-metal, pre-operating system environment. With the Unified Server Configurator (USC) interface, the USC tool provides a single interface that enables efficient operating system deployment with built-in driver installations, firmware updates, hardware configuration, and diagnostics for the system. Servers selected with hot-pluggable hard drives will also get the benefit of an interactive LCD that can be accessed remotely using optional iDRAC Express or iDRAC Enterprise for system alerts and power usage as well as select boot-up options.

Also part of the Dell OpenManage™ portfolio is the Dell Management Console, which is included with every Dell server and provides IT administrators with a consolidated view of their IT infrastructure.

The Dell PowerEdge T310 was designed to meet the needs of your growing small business or remote office.

Feature	Technical Specification
Form Factor	Tower
Processors	Quad-core Intel® Xeon® processors 3400 series or Dual-core Intel® Celeron® G1101, Intel® Pentium® G6950, Dual-core Intel® Core® i3 processor 500 series
Processor Sockets	1
Front Side Bus or HyperTransport	DMI (Direct Media Interface)
Cache	8MB
Chipset	Intel® 3400 chipset
Memory ¹	Up to 32GB (R-DIMM only): Support 6 R-DIMMs or 4 U-DIMMs, 1GB/2GB/4GB/8GB DDR3 800MHz, 1066MHz or 1333MHz
I/O Slots	5 PCIe G2 slots: Two x8 slot, (one with x16 connector) One x4 slot (with x8 connector) Two x1 slots
RAID Controller	Internal: PERC H200 (6Gb/s) PERC H700 (6Gb/s) with 512MB battery-backed cache; 512MB, 1GB Non-Volatile battery-backed cache SAS 6/iR PERC 6/i with 256MB battery-backed cache PERC S100 (software based) PERC S300 (software based) External: PERC H800 (6Gb/s) with 512MB of battery-backed cache; 512MB, 1GB Non-Volatile battery cache PERC 6/E with 256MB or 512MB of battery-backed cache External HBAs (non-RAID): 6Gbps SAS HBA SAS 5/E HBA LSI2032 PCIe SCSI HBA
Drive Bays	Cabled HD options: Up to four 3.5" SAS or SATA drives Hot-Swap HD options: Up to four 3.5" SAS or SATA, or 2.5" SAS or SSD drives
Maximum Internal Storage	4TB
Hard Drives ¹	3.5" SATA (7.2K RPM): 160GB, 250GB, 500GB, 1TB 3.5" Near Line SAS (7.2K RPM) 500GB or 1TB 3.5" 6Gps SAS (7.2K): 2TB 3.5" SAS (10K RPM): 600GB 3.5" SAS (15K RPM): 146GB, 300GB, 450GB 2.5" (7.2K) Nearline SAS 1TB 2.5" SAS (10K RPM): 146GB or 300GB 2.5" SATA SSD 25GB, 50GB 3.5" 2.0TB SATA
Communications	Broadcom® NetXtreme™ 5709 Dual Port Gigabit Ethernet NIC, Copper, w/TOE PCIe x4 Broadcom® NetXtreme™ 5709 Dual Port Gigabit Ethernet NIC, Copper, TOE/iSCSI PCIe x4 Intel® PRO/1000 PT Single Port Adapter, Gigabit Ethernet NIC, PCIe x 1 Intel® Gigabit ET Dual Port Adapter, Gigabit Ethernet NIC, PCIe x4 Intel® Gigabit ET Quad Port Adapter, Gigabit Ethernet NIC, PCIe x4 Intel® Gigabit ET Dual Port Server Adapter and Intel® Gigabit ET Quad Port Server Adapter
Power Supply	Single-cabled power supply (375W)/Optional Redundant power supply (400W)
Availability	Quad-pack LED diagnostic, Interactive LCD with Hot-swap HDD chassis, Hot-swap HDD, Redundant PSU
Video	Matrox® G200eW w/ 8MB memory
Remote Management	iDRAC6
Systems Management	BMC, IPMI 2.0 compliant Dell™ OpenManage™ featuring Dell Management Console Unified Server Configurator Lifecycle Controller enabled via optional iDRAC6 Express, iDRAC6 Enterprise, and vFlash
Operating Systems	Microsoft® Windows® Small Business Server 2008 Microsoft® Windows® Essential Business Server 2008 Microsoft® Windows Server® 2008 SP2, x86/x64 (x64 includes Hyper-V™) Microsoft® Windows Server® 2008 R2, x64 (includes Hyper-V™ v2) Microsoft® Windows® HPC Server 2008 Novell® SUSE® Linux® Enterprise Server Red Hat® Enterprise Linux®
Featured Database Application	For more information on the specific versions and additions, visit www.dell.com/OSsupport . Microsoft® SQL Server® solutions (see Dell.com/SQL)

¹ GB means 1 billion bytes and TB equals 1 trillion bytes; actual capacity varies with preloaded material and operating environment and will be less.

Dell Services

Dell Services can help reduce IT complexity, lower costs, and eliminate inefficiencies by making IT and business solutions work harder for you. The Dell Services team takes a holistic view of your needs and designs solutions for your environment and business objectives while leveraging proven delivery methods, local talent, and in-depth domain knowledge for the lowest TCO.

Learn more at Dell.com/PowerEdge

© 2010 Dell Inc. All rights reserved. Dell, the DELL logo, the DELL badge, PowerEdge, and OpenManage are trademarks of Dell Inc. Other trademarks and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Dell disclaims proprietary interest in the marks and names of others. This document is for informational purposes only. Dell reserves the right to make changes without further notice to any products herein. The content provided is as is and without express or implied warranties of any kind.

