

เอกสารข้อมูลผลิตภัณฑ์

ข้อมูลจำเพาะ



APC Smart-UPS, Line Interactive, 1000VA, Lithium-ion, Rack/Tower, 2U, 230V, 6x IEC C13 outlets, SmartConnect Port+SmartSlot, Short Depth, AVR, LCD

SMTL1000RMI2UC

Overview

Presentation	Intelligent and efficient network power protection from entry level to scalable runtime. Ideal UPS for servers, point-of-sale, routers, switches, hubs and other network devices.
Lead Time	Usually in Stock

Main

Main Input Voltage	230 V
Other Input Voltage	220 V 240 V
Main Output Voltage	230 V
Other Output Voltage	220 V 240 V
Rated Power In W	800 W
Rated Power In Va	1000 VA
Input Connection Type	IEC 60320 C14
Output Connection Type	6 IEC 60320 C13
Number Of Rack Unit	2U
Battery Type	Li-Ion (Lithium-Ion)
Provided Equipment	Installation guide Rack mounting support rails USB cable

Complementary

Software Package	SmartConnect software for remote power monitoring feature availability varies by terms of use
------------------	---

Batteries & Runtime

รันไทม์	View Runtime Graph
ประสิทธิภาพ	View Efficiency Graph
Battery Graph Comments	This graph is based on actual measured runtime data. All measurements were taken with new, fully charged batteries and a balanced resistive load (PF = 1.0). Actual runtimes may vary from the values of this graph. Actual runtimes are dependent on several v
Extended Runtime	0
Battery Recharge Time	3 h
Battery Design Life	8...10 year(s)

Battery Charger Power	79 W rated
-----------------------	------------

General

Product Web Sub-Family	Cloud-enabled monitoring
------------------------	--------------------------

Redundant	No
-----------	----

Physical

Colour	Black with silver front bezel
--------	-------------------------------

Height	8.6 cm
--------	--------

Width	43.8 cm
-------	---------

Depth	31.8 cm
-------	---------

Net Weight	16.3 kg
------------	---------

Mounting Preference	Lower
---------------------	-------

Mounting Mode	Rack-mounted
---------------	--------------

Usb Compatible	Yes
----------------	-----

Input

Input Protection Type	Circuit breaker
-----------------------	-----------------

Input Voltage Limits	151...302 V adjustable 160...280 V
----------------------	---------------------------------------

Network Frequency	50/60 Hz +/- 3 Hz auto-sensing
-------------------	--------------------------------

Output

Crest Factor	3 : 1
--------------	-------

Harmonic Distortion	Less than 5 %
---------------------	---------------

Maximum Configurable Power In Va	1000 VA
----------------------------------	---------

Maximum Configurable Power In W	800 W
---------------------------------	-------

Transfer Time	6 ms typical : 10 ms maximum
---------------	------------------------------

Ups Type	Line interactive
----------	------------------

Wave Type	Sine wave
-----------	-----------

Output Frequency	50/60 Hz +/- 3 Hz sync to mains
------------------	---------------------------------

Conformance

Product Certifications	C-Tick CE EAC RCM
------------------------	----------------------------

Standards	EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018
-----------	--

Environmental

Acoustic Level	41 dBA
----------------	--------

Heat Dissipation	70 Btu/h
------------------	----------

Operating Altitude	0...10000 ft
--------------------	--------------

Ambient Air Temperature For Operation	0...40 °C
---------------------------------------	-----------

Ambient Air Temperature For Storage	-15...45 °C
Storage Altitude	0.00...7620.00 m
Ip Degree Of Protection	IP20
Relative Humidity	0...95 % non-condensing
Storage Relative Humidity	0...95 % non-condensing

Communications & Management

Alarm	Audible and visible alarms
Control Panel	Multifunction LCD status and control console
Free Slots	1
Communication Port Support	SmartConnect Ethernet port: for cloud monitoring feature availability varies by terms of use
Alarm	Alarm when on battery : distinctive low battery alarm

Surge Protection and Filtering

Surge Energy Rate	680 J
Noise Suppression	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	22.9 cm
Package 1 Width	47.2 cm
Package 1 Length	58.4 cm
Package 1 Weight	18.6 kg

Contractual warranty

Warranty	5 year repair or replace
-----------------	--------------------------

ความยั่งยืน

ฉลาก **Green Premium™** เป็นความมุ่งมั่นของ Schneider Electric ในการส่งมอบผลิตภัณฑ์ที่มีประสิทธิภาพด้านสิ่งแวดล้อมที่ดีที่สุด Green Premium ให้คำมั่นว่าจะปฏิบัติตามกฎระเบียบล่าสุด ความโปร่งใสต่อผลกระทบด้านสิ่งแวดล้อม รวมถึงผลิตภัณฑ์หมุนเวียนและ CO₂ ต่ำ

คู่มือการประเมินความยั่งยืนของผลิตภัณฑ์เป็นเอกสารวิจัยที่ช่วยชี้แจงมาตรฐานฉลากสิ่งแวดล้อมทั่วโลกและวิธีการตีความการประเมิน

[เรียนรู้เพิ่มเติมเกี่ยวกับ Green Premium >](#)

[แนวทางในการประเมินความยั่งยืนของผลิตภัณฑ์ >](#)



ความโปร่งใส RoHS/REACH

ประสิทธิภาพด้านสุขภาพ

Mercury Free

Rohs Exemption Information Yes

ใบรับรองและมาตรฐาน

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Compliant with Exemptions

China Rohs Regulation [China RoHS declaration](#)
Product out of China RoHS scope. Substance declaration for your information

Environmental Disclosure [Product Environmental Profile](#)

Weee The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Circularity Profile [End of Life Information](#)