

เอกสารข้อมูลผลิตภัณฑ์

ข้อมูลจำเพาะ



APC Easy UPS On-Line, 6kVA/6kW, Lithium-ion, Rack/Tower 5U, 230V, 1 Hard wire (1P+N+E) outlet, Intelligent Card Slot, Extended runtime, W/ rail kit

SRVL6KRILRK

Overview

Presentation Double-conversion On-line UPS with Lithium-Ion battery to scalable runtime. Ideal UPS for essential power protection needs even in the most unstable power conditions.

Lead Time Usually in Stock

Main

Main Input Voltage	230 V
Other Input Voltage	230 V
Main Output Voltage	230 V
Other Output Voltage	220 V 240 V
Rated Power In W	6000 W
Rated Power In Va	6000 VA
Output Connector Type	Hard wire 3-wire (1P + N + E) 1
Number Of Rack Unit	5U
Provided Equipment	Basic UPS signalling RS-232 cable USB cable RJ45 cable RJ11 cable Battery cable Grounding cable Rack mounting brackets Stabilization feet User manual Safety guide

Batteries & Runtime

รันไทม์	View Runtime Graph
ประสิทธิภาพ	View Efficiency Graph
Battery Type	Li-Ion (Lithium-Ion)
Battery Voltage	48 V
Number Of Battery Filled Slots	0
Number Of Battery Free Slots	0
Battery Recharge Time	5 h
Battery Design Life	8...10 year(s)
Battery Charger Power	1500 W

Physical

Colour	Black with silver front bezel
Height	21.7 cm
Width	43.8 cm
Depth	68.5 cm
Net Weight	69.2 kg
Usb Compatible	Yes
Mounting Position	Horizontal and vertical

Input

Input Voltage Limits	186...300 V full load 120...300 V 60 % load
Number Of Input Connectors	1 hard wire 3-wire (1P + N + E)
Network Frequency	40...70 Hz auto sensing

Output

Maximum Configurable Power In Va	6000 VA
Maximum Configurable Power In W	6000 W
Output Frequency	50/60 Hz +/- 4 Hz sync to mains
Ups Type	Double conversion online
Wave Type	Sine wave
Efficiency	93.5 % (full load)
Bypass Type	Internal bypass (automatic and manual)
Crest Factor	3 : 1

Conformance

Product Certifications	CB CE UKCA RCM IRAM TISI UN 38.3 IEC 62619
------------------------	---

Environmental

Ambient Air Temperature For Operation	0...40 °C
Relative Humidity	0...95 % non-condensing
Operating Altitude	0...3000 m
Ambient Air Temperature For Storage	-20...50 °C
Storage Relative Humidity	0...95 % non-condensing
Storage Altitude	0...15000 m
Acoustic Level	57.3 dBA
Heat Dissipation	1780 Btu/h
Ip Degree Of Protection	IP20

Communications & Management

Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
Emergency Power Off	Yes
Control Panel	Multifunction LCD status and control console

Surge Protection and Filtering

Surge Energy Rate	600 J
-------------------	-------

Packing Units

Unit Type Of Package 1	PCE
------------------------	-----

Number Of Units In Package 1	1
------------------------------	---

Package 1 Height	65.2 cm
------------------	---------

Package 1 Width	60 cm
-----------------	-------

Package 1 Length	80 cm
------------------	-------

Package 1 Weight	85.9 kg
------------------	---------

Contractual warranty

Warranty	3 years UPS repair or replace; 5 years battery repair or replace
----------	--

ความยั่งยืน


ฉลาก **Green Premium™** เป็นความมุ่งมั่นของ Schneider Electric ในการส่งมอบผลิตภัณฑ์ที่มีประสิทธิภาพด้านสิ่งแวดล้อมที่ดีที่สุด Green Premium ให้คำมั่นว่าจะปฏิบัติตามกฎระเบียบล่าสุด ความโปร่งใสต่อผลกระทบต่อสิ่งแวดล้อม รวมถึงผลิตภัณฑ์หมุนเวียนและ CO₂ ต่ำ

คู่มือการประเมินความยั่งยืนของผลิตภัณฑ์เป็นเอกสารวิจัยที่ช่วยชี้แจงมาตรฐานฉลากสิ่งแวดล้อมทั่วโลกและวิธีการตีความการประ

[เรียนรู้เพิ่มเติมเกี่ยวกับ Green Premium >](#)

[แนวทางในการประเมินความยั่งยืนของผลิตภัณฑ์ >](#)

ประสิทธิภาพด้านสุขภาพ

 **Rohs Exemption Information** [Yes](#)

Eu Rohs Directive [Compliant with Exemptions](#)

China Rohs Regulation [China RoHS declaration](#)
Product out of China RoHS scope. Substance declaration for your information
