

เอกสารข้อมูลผลิตภัณฑ์ ลักษณะ

BR1200SI

Back UPS Pro BR 1200VA, Sinewave, 8 Outlets,
AVR, LCD interface



Overview

Lead time Usually in Stock

General

Provided equipment User manual
USB cable

Physical

Colour Black
Depth 36.8 cm
Height 26 cm
Net weight 11.7 kg
Width 10 cm

Input

Network frequency 50/60 Hz +/- 3 Hz auto-sensing
Plug standard IEC 60320 C14
Input voltage limits 176...294 V
Maximum input current 10 A
Switching current capacity 10 A
Input voltage 230 V

Output

Rated power in W 720 W
Maximum configurable power in W 720 W
Output frequency 50/60 Hz +/- 1 Hz sync to mains
UPS type Line interactive

Nb of power socket outlets	6 IEC 60320 C13 2 IEC 60320 C13 surge
Output voltage	230 V

Conformance

Product certifications	A-Tick C-Tick CE EAC RCM TISI
Marking	GS Mark
Equipment protection policy	Lifetime : 200000 AUD Lifetime : 150000 euros Lifetime : 75000 GBP

Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 % non-condensing
Operating altitude	0...10000 ft
Ambient air temperature for storage	-15...45 °C
Storage altitude	0.00...15240.00 m
Acoustic level	45 dBA
Heat dissipation	16 Btu/h

Batteries & Runtime

Battery type	Lead-acid battery
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	16 h
Number of battery replacement quantity	1
Liquid value	0

Communications & Management

Control panel	Multifunction LCD status and control console
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

Surge Protection and Filtering

Surge energy rate	509 J
Noise suppression	Full time multi-pole noise filtering : 10% of IEEE surge let-through : zero clamping response time: instantaneous
Data line protection	RJ45 10/100/1000 Base-T Ethernet protection

Packing Units

Package 1 Weight	13.35 kg
Package 1 Height	35.9 cm
Package 1 width	22.3 cm
Package 1 Length	48.2 cm
SCC14	10731304346897
Number of Units in Package 2	1
Package 2 Weight	14.21 kg
Package 2 Height	228.60 mm
Package 2 width	482.60 mm

Package 2 Length	381.00 mm
------------------	-----------

Offer Sustainability

EU RoHS Directive	Under investigation
-------------------	---------------------

Contractual warranty

Warranty	2 years repair or replace, 3 years repair or replace for European Union countries
----------	---
