

TVS-972XU-I3-4G	
CPU	Intel® Core™ i3-8100 4-core 3.6 GHz Processor
CPU Architecture	64-bit x86
Graphic Processors	Intel® UHD Graphics 630
Floating Point Unit	Yes
Encryption Engine	Yes (AES-NI)
Hardware-accelerated Transcoding	Yes
System Memory	4 GB UDIMM DDR4 (1 x 4GB)
Maximum Memory	64 GB (4 x 16 GB)
Memory Slot	4 x Long-DIMM DDR4
Flash Memory	5GB (Dual boot OS protection)
Drive Bay	4 x 3.5-inch + 5 x 2.5-inch SATA 6Gb/s, 3Gb/s
Drive Compatibility	3.5-inch bays: 3.5-inch SATA hard disk drives 2.5-inch SATA hard disk drives 2.5-inch SATA solid state drives  2.5-inch bays: 2.5-inch SATA solid state drives
Hot-swappable	Yes
SSD Cache Acceleration Support	Yes
Gigabit Ethernet Port (RJ45)	2
10 Gigabit Ethernet Port	2 x 10GbE SFP+ SmartNIC port
Jumbo Frame	Yes
PCIe Slot	1 Slot 1: PCIe Gen 3 x16
USB 3.2 Gen 1 port	2
USB 3.2 Gen 2 (10Gbps) Port	2 x Type-C USB 3.2 Gen 2 5V/3A 10Gbps 2 x Type-A USB 3.2 Gen 2 5V/1A 10Gbps
HDMI Output	1, HDMI 2.0 (up to 3840 x 2160 @ 60Hz)
Form Factor	1U Rackmount
LED Indicators	HDD 1-4, SSD 1-5, Status, LAN

Buttons	Power, Reset
Dimensions (HxWxD)	43.3 × 482.6 × 484.15 mm
Weight (Net)	7.48 kg
Weight (Gross)	10.27 kg
Operating temperature	0 - 40 °C (32°F - 104°F)
Relative Humidity	5-95% RH non-condensing, wet bulb: 27°C (80.6°F)
Power Supply Unit	250W, 100-240V
Power Consumption: Operating Mode, Typical	72.17 W
Fan	System fan: 3 x 40mm, 12VDC
Sound Level	32 db(A)
System Warning	Buzzer

Note: Use only QNAP memory modules to maintain system performance and stability. For NAS devices with more than one memory slot, use QNAP modules with identical specifications. Warning: Using unsupported modules may degrade performance, cause errors, or prevent the operating system from starting.

\* Sound Level Test Environment: Refer to ISO 7779; Maximum HDD loaded; Bystander Position; Average data from 1 meter in front of operating NAS.

Designs and specifications are subject to change without notice.